


PORTABLE LIGHTS FOR INDUSTRIAL & EMERGENCY APPLICATIONS

IN - Range of Portable Lighting

Models: IN120L • IN120LB • IN2400LB

The IN120L & IN120LB Industrial are the most common of our EXIN Light Portable Lighting Range. Producing 1030 lumens each side of the Light Head, the IN120L operates continuously on a single charge for up to twelve (12) hours on one side of the Light Head, and the IN120LB running continuously for up to thirty (30) hours on a single charge on one side of the Light Head.

The IN2400L Light Head has three power settings (high, medium and low) to suit different applications. It produces 2400 lumens from the single-sided Light Head on the high setting. This powerful light is made up of high quality LEDs (20x1 watt LEDs), fitted with an Emergency Flash Function and can be tilted by 60° to light up a wide area.



LIGHTHEAD

With its Light Head tilting down by up to 60° the IN120L and IN120LB can be used for area illumination, Flash Functions and can easily illuminate a large open space with its 2060 lumens, with little or no heat produced from the EXIN Light it allows you to work in close proximity with comfort.

BODY

The IN120L and IN120LB Body is exactly the same, it is constructed using an automotive type ABS747 making the light highly durable with its robust solid construction. The EXIN Light IN Series has an IP 65 rating, and also is manufactured with a UV and Salt Water resistant ingredient, allowing the use in both wet and dry environments. Using shock absorbing rubber for both the Base and Lid Seals gives extra added protection to your Light Head and Base. With Extension Arms fitted either side of the Body and a push and pull Functional Handle, enables you to choose the correct height suited to your own individual needs.

BATTERY

The IN120L is powered by a 9AH Lead Acid Gel Battery taking only 7-8 hours to fully charge. The IN120LB & IN2400LB are powered by an 18AH Lead Acid Gel Battery taking only 12-14 hours to fully charge.

SPECIFICATIONS

Model	IN120L Industrial	IN120LB Industrial	IN2400L Industrial
Net Weight (kg)	8.1	11.1	12.0
Gross Weight (kg)	9.5	12.6	12.6
Open Height (mm)	1120	1120	1120
Closed Height (mm)	580	580	580
Width (mm)	340	340	340
Depth (mm)	250	250	250
Charging Voltage AC/DC	100-240V 12/24V Optional Solar Panel	100-240V 12/24V Optional Solar Panel	100-240V 12/24V Optional Solar Panel
Light Type LED	Double Sided	Double Sided	One Side
Lumens (lm)	1030 each side	1030 each side	<ul style="list-style-type: none"> • Low - 600 • Med - 1200 • High - 2400
Battery Run Time (hrs)	<ul style="list-style-type: none"> • One Side - 10-12 • Both Sides - 5-6 	<ul style="list-style-type: none"> • One Side - 20-24 • Both Sides - 10-12 	<ul style="list-style-type: none"> • Low - 48 • Med - 16 • High - 8
Battery Charge Time (hrs)	7-8	12-14	12-14



Australian Made & Designed.

